



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE: BACKLIGHT**

**DESCRIPTION** : PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

**COMPOSITION** : 69 % PVC  
31 % POLYESTER

**WIDTH** : 137 - 150 - 202 - 220 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.42	
TOTAL MASS (g/m <sup>2</sup> )	450 ± 40	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	140 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 250 T.: 170	EN ISO 1421
BREAKING EXTENSION (%)	L.: 18 T.: 20	EN ISO 1421
TEAR STRENGTH (daN)	L.: 22.0 T.: 18.0	DIN 53363
COATING ADHESION (daN/50mm)	min 5.0	EN ISO 2411
COLOUR FASTNESS TO LIGHT	min 5	EN ISO 105-B02
AVERAGE LIGHT TRANSMISSION	18	SF 600 Plus Spectrophotometer
FLAMMABILITY (mm/min)	< 100	DIN 75200

L - Along

T - Across

**NOTE** : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2009.10.19	8		