



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: GLOSS 650 2L

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

COMPOSITION : 76 % PVC
24 % POLYESTER

WIDTH : 150 – 220 – 250 – 300 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.54	
TOTAL MASS (g/m ²)	650 ± 50	EN ISO 2286-2
FABRIC MASS (g/m ²)	155 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 240 T.: 200	EN ISO 1421
TEAR STRENGTH (daN)	L.: 15 T.: 20	EN ISO 4674-1B
COATING ADHESION (daN/50mm)	min. 7.5	EN ISO 2411

L - Along
T - Across

NOTE: This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.12.06	2		