



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: PRINT MP 90 FR

DESCRIPTION: PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM

COMPOSITION: 58 % PVC
42 % POLYESTER

WIDTH : 160 - 250 - 320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.65	
TOTAL MASS (g/m ²)	480 ± 40	EN ISO 2286-2
FABRIC MASS (g/m ²)	200 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 270 T.: 270	EN ISO 1421
TEAR STRENGTH (daN)	L.: 35 T.: 40	DIN 53363
COATING ADHESION (daN/50mm)	min 7.5	EN ISO 2411
BURNING BEHAVIOUR	B1	DIN 4102
BURNING BEHAVIOUR	M2	NF P92-503

L – Along T – Across

NOTE: This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2011.02.04	2		