



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE: PRINT MS 74**

**DESCRIPTION** : PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM

**COMPOSITION** : 57 % PVC  
43 % POLYESTER

**WIDTH** : 160 – 250 -320 - 500 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.37	
TOTAL MASS (g/m <sup>2</sup> )	340 ± 30	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	145 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 240 T.: 140	EN ISO 1421
BREAKING EXTENSION (%)	L.: 22 T.: 22	EN ISO 1421
TEAR STRENGTH (daN)	L.: 35 T.: 15	DIN 53363
COLOUR FASTNESS TO LIGHT	min 6	EN ISO 105-B02
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m <sup>2</sup> /s)	1690	EN ISO 9237
AVERAGE LIGHT TRANSMISSION	22	SF 600 Plus Spectrophotometer
OPEN AREA (%)	11	Internal

L – Along T – Across

**NOTE** : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2010.03.09	2		