

ficha técnica

Eco flag 117 FR

genero de punto

número de artículo: 3745-6
materia: 100 % PES
peso: 117 g/m²

especialidades:

muy suave
anti rasgado
transparente
óptima difusión en la impresión
anti deshilachado
antiestático
rolls boxed on demand

aplicaciones:

banderas
banderas de playa
banners

observaciones:

New: now with antistatic coating / Detailed information see flag navigator (web side) / Ideal para sublimación directa con calandra incorporada.

compatibilidades del producto:

Eco flag 117 FR es compatible para las siguientes impresoras (método de impresión)

HP Latex LX 800/ 820/ 850 (Latex)	Durst Rhotex 320 (Sub water)
Agfa Aquajet (Sub water)	D.gen Grande (Sub water)
Mimaki DS series (Sub water)	Paper Transfer (Sub Paper)
Durst Rho UV series (UV curable)	EFI GS series (UV curable)
EFI LX series (LED)	

propiedades del producto:



www.bergertextil.com

++ 49 2151 65231-0

ficha técnica

Eco flag 117 FR

resultado de las pruebas:

NUR Expedio Bending

Extended Tests at Nur in Belgium brought the following results and solutions:

Bending is not a material problem

1. Bending over the full width: Calibration issue
2. Bending on the right and left edges: tension/traction adjustment
3. Bending on sample rolls ca.1m, are caused by the elastic material. This won't happen with regular 300/ 500 cm rolls

Test Mimaki:

Mimaki /Mitex with sensient inks: Ok / printhrough ok

Mimaki with origanl mimaki inks: Ok / Printhrough ok

Dyesubdirectprint with TX2, Artistri ,Dgen Teleios etc:

coated flag (+W) reaches good colordefinition and brillianz, the printhrough can be maximised with increasing the ink. The printhrough gets generally better with uncoated flag by loss of colorbrilliance. For Dgen Teleios we recommend uncoated flag, for Artistri/Tx2 coated flag.

Material safety Information

Possible risks: not known

Handling: Sufficient ventilation/aspiration of the work place has to be provided

Storage: to be stored dry and close

Toxicology: To be kept away from eyes and mouth, further information are given on the technical data sheets of the flame retardant.

Disposal: domestic waste, for big quantities pls. pay attention to the technical data sheets of the flame retardant.

ficha técnica

Eco flag 117 FR



Kuhleshütte 84
47809 Krefeld
Germany


teléfono: +49 (0)2151 65231-0

Fax: +49 (0)2151 65231-25

Email: info@bergertextil.com

Internet: www.bergertextil.com

Imagen del producto:



www.bergertextil.com

++ 49 2151 65231-0

la información de esta hoja de información está basada en valores obtenidos de la práctica. Debido a la gran cantidad de factores que se pueden dar durante la manipulación y aplicación. Es necesario que el cliente haga pruebas. No se tendrá en consideración.